

# Product specification

1		<b>Pfeifer cable tension member PV</b>
1.1	1,00 pc	<p>Pfeifer cable tension member PV consisting of: 1 pc fatigue-resistant open spelter socket type 700, 1 pc adjustable fatigue-resistant open spelter socket type 710, 1 pc full locked cable with GALFAN coating.</p> <p>Fabricated according to European Technical Assessment ETA-11/0160 as pre-assembled cable system with product specific label.</p> <p><b>System size:</b> PV 40 / PV 60 / PV 90 / PV 115 / PV 150 / PV 195 / PV 240 / PV 300 / PV 360 / PV 420 / PV 490 / PV 560 / PV 640 / PV 720 / PV 810 / PV 910 / PV 1010 / PV 1110 / PV 1220 / PV 1340 / PV 1450 / PV 1580 / PV 1730 / PV 1860 / PV 2000</p> <p><b>System length</b> (from pin center to pin center) [m]: XXX,XX</p> <p>Or equivalent.</p>
1.2	1,00 pc	<p>Pfeifer cable tension member PV consisting of: 1 pc fatigue-resistant open spelter socket type 700, 1 pc conical socket type 800, 1 pc full locked cable with GALFAN coating.</p> <p>Fabricated according to European Technical Assessment ETA-11/0160 as pre-assembled cable system with product specific label.</p> <p><b>System size:</b> PV 40 / PV 60 / PV 90 / PV 115 / PV 150 / PV 195 / PV 240 / PV 300 / PV 360 / PV 420 / PV 490 / PV 560 / PV 640 / PV 720 / PV 810 / PV 910 / PV 1010 / PV 1110 / PV 1220 / PV 1340 / PV 1450 / PV 1580 / PV 1730 / PV 1860 / PV 2000</p> <p><b>System length</b> (from pin center to face of conical socket) [m]: XXX,XX</p> <p>Or equivalent.</p>