

# Product specification

<b>1</b>		<b>Pfeifer Tension Rod System type UMIK</b>
<b>1.1</b>	<b>1,00 pc</b>	<p>Pfeifer tension rod system type UMIK Stainless Steel consisting of: 1 pc. fork end RHT, incl. pin and lock nut RH, 1 pc. fork end LHT, incl. pin and lock nut LH, 1 pc. tension rod with thread on both sides.</p> <p>As pre-assembled tension rod system with product-specific label.</p> <p><b>System size:</b> 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048 / 052 / 056 / 060 / 064 / 070 / 080 / 090 / 100</p> <p><b>System length</b> (from pin center to pin center) [m]: XXX,XX</p> <p>Or equivalent.</p>
<b>1.2</b>	<b>1,00 pc</b>	<p>Pfeifer tension rod system type UMIK Stainless Steel with adapter consisting of: 2 pc. fork end RHT, incl. pin and lock nut RHT, 1 pc. adapter RHT/LHT, 1 pc. tension rod with thread on both sides.</p> <p>As pre-assembled tension rod system with product-specific label.</p> <p><b>System size:</b> 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048 / 052 / 056 / 060 / 064 / 070 / 080 / 090 / 100</p> <p><b>System length</b> (from pin center to pin center) [m]: XXX,XX</p> <p>Or equivalent.</p>
<b>1.3</b>	<b>1,00 pc</b>	<p>Pfeifer tension rod system type UMIK Stainless Steel with coupler/intersection coupler/ connector consisting of: 1 pc. fork end RHT, incl. pin and lock nut RH, 1 pc. fork end LHT, incl. pin and lock nut LH, 1 pc. coupler incl. lock nuts RHT/LHT/intersection coupler incl. lock nuts RHT/LHT/connector, 2 pcs. tension rod with thread on both sides.</p> <p>As pre-assembled tension rod system with product-specific label.</p> <p><b>System size:</b> 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048 / 052 / 056 / 060 / 064 / 070 / 080 / 090 / 100</p> <p><b>System length</b> (from pin center to pin center) [m]: XXX, XX</p> <p>Joint position (pin center to center of coupler)/connector position (pin center to center of connector) [m]: XXX, XX</p> <p>Or equivalent.</p>
<b>1.4</b>	<b>1,00 pc</b>	<p>Pfeifer tension rod systems type UMIK Stainless Steel with intersection plate consisting of: 4 pcs. fork end RHT incl. pin and lock nut RHT, 4 pcs. fork end LHT incl. pin and lock nut LH, 1 pc. intersection plate, 4 pcs. tension rod with hot-dip galvanized thread on both sides.</p> <p>As pre-assembled tension rod system with product-specific label.</p> <p><b>System size:</b> 008 / 010 / 012 / 014 / 016 / 020 / 024 / 027 / 030 / 036 / 042 / 048 / 052 / 056 / 060 / 064 / 070 / 080 / 090 / 100</p> <p><b>System diagonal length</b> (pin center to pin center) [m]: XXX,XX</p> <p>Opening angle (40–90°) [°]: XXX, XX</p> <p>Or equivalent.</p>